



Simplify with SimplyGo

SimplyGo is the only portable oxygen concentrator (POC) to offer continuous flow and pulse-dose delivery in one lightweight device, weighing only ten pounds. That means you can now manage the therapy and lifestyle needs of nearly all of your patients with just one POC. If you could benefit by simplifying patient management—and your business—then look no further than the SimplyGo portable oxygen concentrator from Philips Respironics.

Built-in reliability

SimplyGo strives to set a new standard in POC reliability. Designed, built, and rigorously tested to withstand the bumps and bangs of everyday life, SimplyGo can be counted on to perform reliably in real-world use day in and day out. That should mean fewer call backs for you and fewer frustrations for your patients due to accidental damage.

The SimplyGo portable oxygen concentrator:

- Has continuous flow (2 LPM), pulse dose, and sleep modes
- Weighs 10 lbs
- Offers a choice of warranties
- Is pending FAA approval

PHILIPS

RESPIRONICS

sense **and** simplicity

SimplyGo specifications

Product specifications			
Oxygen concentrations*	87 to 96% at all settings		
Outlet pressure	3 PSI		
Flow settings and pulse volumes			
Pulse mode bolus size	1 = 12 ml, 1.5 = 18 ml, 2 = 24 ml, 2.5 = 30 ml, 3 = 36 ml, 3.5 = 42 ml, 4 = 48 ml, 4.5 = 54 ml, 5 = 60 ml, 5.5 = 66 ml, 6 = 72 ml +/- 10% or 3 ml whichever is greater (average of 20 consecutive breaths) up to a max of 2000 ml/min +/- 200 ml		
Continuous flow settings	0.5 LPM, 1 LPM, 1.5 LPM, 2 LPM +/- 10% or 100 ml/min whichever is greater (3 minute running average)		
Sound level	≤43 dB (nominal) at pulse setting 2		
Physical characteristics			
Size	11.5 in x 10 in x 6 in (29.2 cm x 25.4 cm x 15.2 cm)		
Weight	10 lbs (4.5 kg) with battery installed		
User interface	Push buttons, back-lit liquid crystal display (LCD)		
Filtration	Internal: air inlet filter (gross particle), main-flow bacteria filter		
Operating conditions			
Operational temperature	41° to 104°F (5° to 40°C)		
Relative humidity	15 to 95%		
Altitude	Up to 10,000 ft (3048 m)		
Storage conditions			
Temperature	-4° to 140°F (-20° to 60°C) unit only		
Relative humidity	Up to 95%, non condensing		
AC power			
Input	100 to 240 VAC, 50/60 Hz, 2.0 A		
Output	19 VDC 7.9 A max		
Power consumption	150W while charging 120W while not charging		
DC power			
Input	12 to 19 VDC 8.0 A max		
Audible alarm			
Sound level	50 dB (nominal) at 39 in (1 m)		
Alarm type	Low oxygen purity, No breath, High breath rate, No flow, Low battery, Depleted battery, Wrong battery, System technical fault		
Battery			
Chemistry	Lithium Ion 14.4 VDC (nominal)		
Dimensions	0.9" x 7.4" x 4.6" (2.7 cm x 18.8 cm x 11.7 cm)		
Weight	1.5 lbs (0.7 kg)		
Charge time	Approximately 2 to 3 hours per battery from fully discharged		
Battery duration			
Number of batteries	Pulse dose setting of 2**	Continuous flow 1 LPM	Continuous flow 2 LPM
1	3.5 hours	2.3 hours	.7 hours
2	7 hours	4.6 hours	1.4 hours
3	10.5 hours	6.9 hours	2.1 hours
4	14 hours	9.2 hours	2.8 hours

* Based on an atmospheric pressure of 14.7 psia (101 kPa) at 70°F (21°C)

** Based on 20 breaths per minute

Ordering information

SimplyGo system	
Basic system	1068987
Includes SimplyGo portable oxygen concentrator, carrying case, mobile cart, one rechargeable Lithium Ion battery, DC and AC power cords, accessory bag, and user manual	
Combination systems	
SimplyGo/EverFlo non-OPI	1097735
SimplyGo/EverFlo OPI	1097736
SimplyGo/EverFlo Q non-OPI	1098608
SimplyGo/EverFlo Q OPI	1097737
Accessories	
SimplyGo carrying case	1082663
Lithium Ion battery	1082662
Battery charger	900-103
DC power supply	1083692
AC power supply and cord	1082661
Airline power cord	1083693
Accessory bag	1083696
Mobile cart	1074885
User manual	1083700
Humidifier pouch	1083699
Humidifier connecting tube	1039642

Reimbursement information

HCPCS code	Equipment	Description
E1390	Oxygen concentrator—single delivery port	Single delivery port, capable of delivering 85% or greater oxygen concentration at the prescribed flow rate, each
E1392	Portable oxygen concentrator, rental	Reimbursement at the standard portable system add-on rate, provided medical necessity for a portable oxygen system is met

Warranties

Options	
SimplyGo two-year total warranty	1097623
SimplyGo three-year total warranty	1097577
SimplyGo five-year total warranty	1097778

**Philips Healthcare is part of
Royal Philips Electronics**

How to reach us

www.philips.com/healthcare
healthcare@philips.com

Asia
+49 7031 463 2254

Europe, Middle East, Africa
+49 7031 463 2254

Latin America
+55 11 2125 0744

North America
+1 425 487 7000
800 285 5585 (toll free, US only)

Philips Respironics
1010 Murry Ridge Lane
Murrysville, PA 15668

Customer Service
+1 724 387 4000
800 345 6443 (toll free, US only)

Philips Respironics International
Headquarters
+33 1 47 28 30 82

Philips Respironics Asia Pacific
+65 6882 5282

Philips Respironics Australia
+61 (2) 9666 4444

Philips Respironics China
+86 400 828 6665
+86 800 828 6665

Philips Respironics Deutschland
+49 8152 93 06 0

Philips Respironics France
+33 2 51 89 36 00

Philips Respironics Italy
+39 039 203 1

Philips Respironics Sweden
+46 8 120 45 900

Philips Respironics Switzerland
+41 6 27 45 17 50

Philips Respironics United Kingdom
+44 800 1300 845

www.philips.com/respironics

Respironics, EverFlo, and SimplyGo are trademarks of Respironics, Inc. and its affiliates. All rights reserved.

Please visit www.philips.com/simplygo



© 2012 Koninklijke Philips Electronics N.V.
All rights are reserved.

Philips Healthcare reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

WMB 01/09/12 MCI 4104703